

HOW TO CARE FOR YOUR WRAP

LIFTING / HAULOUT

Prior to having the vessel lifted, the owner / crew must inform the boat yard of the vinyl wrap and make arrangements to protect the surface during lifting and storage. Typically the film will reach optimum adhesion after 3 days. Do not launch the boat into the water before this time has elapsed

FENDERS

Rubber fenders are recommended to have soft covers / socks to protect the vinyl surface. This can reduce the potential of mechanical friction

CLEANING

It is recommended to wash the vinyl regularly. The best way to clean the wrap is by hand using only soapy water and a sponge then rinse with clean fresh water. Do not use stiff or hard brushes and abrasive cleaners. This can damage the surface. Never use solvents or buff the wrap. Any wax application must be approved by the applicator.

Pressure washing is not the best practice but may be used following these guidelines:

- a. Nozzle pressure should not exceed 1,300 PSI
- b. Water temperature should not exceed 60°C
- c. Nozzle tip should not be closer than 5" from wrap film
- d. Angle of water spray should be no shallower than 60 degrees from perpendicular
- e. Post washing, fresh water rinse will help maintain the life of wrap film.

FUEL SPILLS

Any fuel spills must be washed off immediately with soapy water to avoid damage to the surface

REPAIRS

If damage has occurred the vinyl can be patch repaired. Repairs will be visible from up close but further away will blend in.

ADDITIONAL INFORMATION

For additional care and maintenance information please contact your installer



Caring for Your Vehicle Graphics & Wraps

Care for your vehicle graphics like you would any fine paint finish. Using high quality products designed specifically for car care and these cleaning and maintenance procedures will help keep your 3M vehicle wraps looking their best.

1. Wash regularly

- Wash whenever the car appears dirty. Contaminants allowed to remain on the vehicle wrap may be more difficult to remove during cleaning.
- Rinse off as much dirt and grit as possible with a spray of water.
- See item 4, Difficult contaminants, for spot cleaning bird droppings, tar, etc.
- Use a wet, non-abrasive detergent such as 3M™ Car Wash Soap 39000 or Meguiar's NXT Generation® Car Wash or Deep Crystal® Car Wash and a soft, clean cloth or sponge.
- Rinse thoroughly with clean water. To reduce water spotting, immediately use a silicone squeegee to remove water and finish with a clean microfiber cloth.

2. Automated car washes

Brush-type car washes are not recommended as they can abrade the film and cause edges to lift or chip, as well as dulling the film's appearance. Brushless car washes are acceptable.

3. Pressure washing

Although hand washing is the preferred cleaning method, pressure washing may be used under these conditions.

- Ensure the water pressure is kept below 2000 psi (14 MPa).
- Keep water temperature below 80°C (180°F).
- Use a spray nozzle with a 40 degree wide angle spray pattern.
- Keep the nozzle at least 1 foot (300 mm) away from and perpendicular (at 90 degrees) to the graphic.

Important Note!

Holding the nozzle of a pressure washer at an angle to the graphic may lift the edges of the film.

4. Difficult contaminants

Soften difficult contaminants such as bug splatter, bird droppings, tree sap and similar contaminants by soaking them for several minutes with very hot, soapy water. Rinse thoroughly and dry. If further cleaning is needed, test one of these products in an inconspicuous area to ensure no damage to the wrap film: Meguiar's Gold Class™ Bug and Tar Remover or 3M™ Citrus Base Cleaner. Isopropyl alcohol (IPA) (two parts IPA to 1 part water) or denatured alcohol may also help. Spot clean the contaminants. Do not use rough scrubbing or abrasive tools, which will scratch the film. Wash and rinse off all residue immediately.

5. Fuel spills

Wipe off immediately to avoid degrading the vinyl and adhesive. Then wash, rinse and dry as in Item 1 as soon as possible.

6. Store indoors or under cover whenever possible

Wrap films (just like paint) are degraded by prolonged exposure to sun and atmospheric pollutants, particularly on the horizontal surfaces such as hood, trunk lid and roof. Whenever possible, store in a garage or at least in a shaded area during the day. At night, protect the car from dew or rain, which may contain acidic pollutants (a common problem in many large metropolitan areas). When a garage is not available, consider using a cloth car cover at night. If your wrap film starts to discolor or turn brown (which is caused by acidic pollution), immediately have a professional remove the wrap film from the vehicle to avoid staining the underlying paint.

7. Film restoration

The following restoration recommendations will help keep your vehicle wraps looking their best.

- Do not use any abrasive polishes or cutting compounds.
- Do not use any polishing or wax products on matte or textured films.
- Use if there is wax or wax residue on the surface, remove with an all-purpose cleaner.
- Table 1 shows some available products to help restore your vehicle wrap. Before using, always test and approve in an inconspicuous area.

TABLE 1
Restoration Alternatives

Film or Finish Type	Product or Solution
Smooth Gloss Texture	3M™ Perfect-it™ Show Car Paste Wax 39526 Meguiar's Gold Class™ Carnuaba Plus Premium Liquid Wax
Matte or Satin Texture	Isopropyl alcohol and water (ratio 2:1)
Matte White (1080-M10) Carbon Fiber White (1080-CF10)	Based on type/degree of contamination, use one or more of these solutions, <i>in the order shown</i> , to remove any build-up: <ol style="list-style-type: none"> 1. Hot, soapy water solution 2. Isopropyl alcohol (IPA) and water (ratio 2:1) 3. Simple Green® All-Purpose Cleaner 4. Household chlorine bleach; followed by IPA/water (#2) 5. Mineral spirits; followed by IPA/water (#2)
Carbon Fiber or Brushed Metal Texture	3M™ Tire Restorer or Meguiar's Natural Shine Protectant
Carbon Fiber Black (1080-CF12)	Meguiar's Ultimate Black Plastic Restorer

8. Visit us on the web!

For complete information about 3M products and warranties, please go to: www.3Mgraphics.com.

3M and Perfect-it are trademarks of 3M Company in the United States and other Countries.
Gold Class, Deep Crystal, Meguiars and NXT Generation are trademarks or registered trademarks of Meguiars, Inc.



Commercial Graphics

3M Center, Building 220-12E-04
St. Paul, MN 55144 USA
General & Technical
1-800-328-3908
Fax 1-651-736-4233

www.3Mgraphics.com

3M Canada

PO Box 5757
London, Ontario
Canada N6A 4T1
General 1-800-265-1840
Fax 519-452-6245

3M México S.A. de C.V.

Av. Santa Fe No. 55
Col. Santa Fe, Del. Alvaro Obregón
México D.F. 01210
General 5255-5270-0400
Fax 5255-5270-2277

3M Puerto Rico, Inc.

350 Chardon Avenue
Suite 1100
San Juan, PR 00918
General 787-620-3000
Fax 787-620-3018

©3M 2012. All rights reserved.